


Plastic Luminaire 2x18 to 3x36 Watt

Type of Explosion Protection:

 II 2G Ex deq IIC T4/T3 -20°C ≤ T_a ≤ +40/50°C

 II 2D Ex tD A21 IP 6X T 80 °C

Degree of Enclosure Protection: IP 66



EC-Type Examination Certificate:

IBExU 97 ATEX 1035

Description:

- Plastic enclosure with plastic heads
- Light and compact design (from 5.5 kg)
- Sturdy impact-proof plastic
- Aluminium mirror reflector
- Lamp cover polycarbonate uv-resistant
- 2-pin-G13-sockets spring-mounted taking up to 100 Hz
- Hole-to-hole spacing variable
- Two cable entries M 25 x 1.5 as standard

Type	Nominal Voltage	Wattage	Dimensions (mm)	Art. No./ Order-No.
BS 809200	230 V	2x18 W	730x183x130	809200
BS 819200	230 V	3x18 W	730x183x130	819200
BS 839200	230 V	2x36 W	1340x183x130	839200
BS 849200	230 V	3x36 W	1340x183x130	849200

Hole-to-Hole Spacing:

L_{plastic (2x18)} = 200 to 400 mm

L_{plastic (2x36)} = 580 mm (adjustable from 800 to 1000 mm)

Polar Curves of Light Distribution on Request