



## LED Modern Art II


This luminaire is applied everywhere where features shall be accentuated. With its modern, but also timeless design this luminaire fits into existing urban structures.

Equipped with proven single-chip technology with **nominal 90 lm/W** at 6000 K these luminaires provide pleasant light in many fields of application.

### Typical Application Areas:

(Lighting Classes)

ME2	<input type="checkbox"/>	S2	<input type="checkbox"/>
ME3	<input type="checkbox"/>	S3	<input type="checkbox"/>
ME4	<input type="checkbox"/>	S4	<input checked="" type="checkbox"/>
ME5	<input type="checkbox"/>	S5	<input checked="" type="checkbox"/>
ME6	<input type="checkbox"/>	S6	<input checked="" type="checkbox"/>



- Enclosure: cast aluminium powder coated (black RAL 9017)
- Illuminant cover: single-pane safety glass
- Recommended pole height: 3.5 m – 6.0 m
- Single-chip-LED
- Light distribution: symmetrical
- Colour temperature: 6000 K
- Life time LED: 50,000 h – L70, B10
- Degree of protection IP 65

### **Model description and performance variants**

Model	Description	Performance	Weight Luminaire head	Wind load	Effective lumen output (at 6000 K)
<b>1000316</b>	Modern Art II	55W	9.5 kg	0.15 m <sup>2</sup>	3161

Subject to technical modifications

Part 3 Page 22

19.11.2015