

## LED Ceiling Light Silverlight Model 941

The LED Ceiling Light Silverlight is excellently suited for mounting in plasterboard ceilings, on concrete ceilings, or as pendant luminaire – and therefore is used in offices, conference rooms, salesrooms, as well as schools and libraries. For surface mounting an aluminium profile frame, 50 mm high, is required which can be ordered as an accessory. Through the pane of frosted glass the LED are not visible and, thus, they produce an even light distribution.



- Enclosure: aluminium
- Illuminants: LED
- Light distribution: symmetrical
- Colour temperatures: neutral white (4,000 K)
- Connecting cable 2 m
- Service life: 50,000 hours
- Ambient temperature: from -20°C to +50°C
- Energy label A+

Model description and performance variants							
Model	Description	Dimensions in mm	Performance	Colour temperature	Weight	Lumen output per Watt	Effective lumen output
941-18	LED Ceiling Light Silverlight	295 x 295	18 W	4,000 K	1.25 kg	92 lm/W	1,650 lm
941-36	LED Ceiling Light Silverlight	1,195 x 295	36 W	4,000 K	3.5 kg	87.5 lm/W	3,150 lm
941-40	LED Ceiling Light Silverlight	595 x 595	40 W	4,000 K	4.1 kg	85 lm/W	3,400 lm
941-72	LED Ceiling Light Silverlight	1,195 x 595	72 W	4,000 K	9.0 kg	78 lm/W	5,600 lm

Subject to technical modifications

Part 4 Page 15

01.09.2015



## Accessories for LED Ceiling Light Silverlight Model 941:

**OPTIONALLY available:**

### **MOUNTING – PLASTERBOARD CEILING**

The LED panel can be mounted in the plasterboard ceiling by means of mounting clips (item numbers see table). Depending on the size of the panel 4 or 6 mounting clips are required; for panels 30 x 30 cm, 60 x 60 cm and 120 x 30 cm 4 mounting clips are needed and for a panel 120 x 60 cm 6 mounting clips are required.

### **MOUNTING – CONCRETE CEILING**

For surface mounting on a concrete ceiling aluminium profiles (50 mm high) are required (item numbers see table).

### **PENDANT INSTALLATION**

Pendant installation is possible for all types of ceilings, but only suited for the panel sizes 595 x 595 mm, 1195 x 295 mm and 1195 x 595 mm. It is recommended to apply triangular suspension. This prevents the luminaire panels from swaying (item numbers see table).

<b>Plasterboard ceiling</b>	Size in mm	Item no.
Mounting clips 4 pcs.	For 300 x 300, 600 x 600, 1200 x 300	941-KL-4
Mounting clips 6 pcs.	For 1200 x 600	941-KL-6
<b>Concrete ceiling</b>		
Aluminium profile white, 50 mm, 295 x 295	For 300 x 300	941-ALU-295x295
Aluminium profile white, 50 mm, 595 x 595	For 600 x 600	941-ALU-595x595
Aluminium profile white, 50 mm, 1195 x 295	For 1200 x 300	941-ALU-1195x295
Aluminium profile white, 50 mm, 1195 x 595	For 1200 x 600	941-ALU-1195x595
<b>Pendant installation</b>		
Mounting kit	For 600 x 600, 1200 x 300, 1200 x 600	941-PM

Subject to technical modifications

Part 4 Page 16

01.09.2015